

# EPC-5120

无风扇嵌入式系统

AMD Geode™ CS5536; 支持1个Mini-PCI槽



## 产品规格

### >> 系统架构

结构	无风扇设计铝制机壳
处理器	Supports AMD Geode™ LX800 500 MHz with 128 KB L2 cache AMD Geode™ CS5536 companion chip
内存	1 x 184-pin Non-ECC Non-Registered DDR DIMM, Max up to 1 GB
扩展槽	1 x PCI104 (without -12 V and -5 V) 1 x Mini-PCI 槽
前面板I/O分布	HDD Access/Power/LAN status LED (Act/Link; Speed) Programmable Alarm LED Programmable Status LED 4 x USB 2.0 ports 2 x Serial ports
后面板I/O分布	1 x Parallel port 1 x PS/2 Keyboard/Mouse 1 x IEEE1394 port 2 x Serial ports 1 x Audio out 2 x 10/100 Ethernet LAN 1 x VGA connector 1 x DC power +12 V input
存储	1 x On-board CompactFlash socket 1 x Internal 2.5" HDD drive bay
电源输入	1 x External 60 W AC adapter Power input: 100 ~ 240V AC 2 A 50/60 Hz Power output: 12 VDC
尺寸	195 mm (W) x 150 mm (D) x 80 mm (H)

### >> 产品特点

- ▶ 支持AMD Geode™ LX800 400/500 MHz with 128 KB L2 Cache
- ▶ AMD Geode™ CS5536 Companion Chip
- ▶ 双 10/100 以太网
- ▶ 4 x USB 2.0/VGA/IEEE 1394/Audio Out 接口
- ▶ 板载Mini-PCI 槽作为无线网络连接
- ▶ 4 x 串口, 支持RS232

### >> 环境参数

工作温度	常温: 0°C ~ 40°C Tcase (Surface Temperature of Chassis) 5° C to 40° C (W/HDD) -10° C ~ 45° C (W/CF card only)
储存温度	-20°C ~ 80°C
相对湿度	10% ~ 90% (无凝露)

### >> 订购信息

EPC-5120	AMD Geode™ CS5536 Companion Chip 1 x Mini-PCI 槽; 100 ~ 240V AC 电压输入
----------	--

### >> 产品尺寸

(单位: mm)

外型尺寸

